



## Dome GX2MP

Superb Visual Quality.

DICOM calibrated.

### FEATURES:

- > High Performance 20.1" 2 megapixel LCD panel
- > Superior visual quality with .255mm pixel pitch
- > 16 ms response time
- > Outstanding 1000:1 contrast ratio
- > 300 cd/m<sup>2</sup> luminance
- > Height adjustable stand helps reduce eye and neck strain allowing each user to adjust the height of this LCD monitor to their exact comfort level
- > Dome CXtra™ for DICOM Calibration



> Outstanding 1000:1 Contrast Ratio



> Enterprise Management and DICOM Conformance with Dome CXtra

The Dome GX2MP is a high-quality color display intended for use in a clinical environment. The GX2MP offers a 1200 x 1600 resolution, superior visual quality, and superb performance at an incredibly fast 16ms response time and comes DICOM calibrated with Dome CXtra software. With Dome CXtra, Dome GX2MP users also receive manual DICOM calibration with an external photometer, test patterns, reporting, backlight saver and enterprise management functions. In addition the GX2MP comes complete with graphics hardware and the necessary cables, everything the end user will need for an easy installation.





<b>SPECIFICATIONS:</b>	
<b>LCD DISPLAY</b>	
Technology	TFT AMLCD MVA, 3 subpixels per pixel
Screen diagonal	20.1-inch (510.5mm)
Display Resolution	1600x1200 landscape, 1200x1600 portrait
Pixel Pitch	.255 mm
Viewing angle (CR 10:1)	+/- 85° (170°) horizontal +/- 85° (170°) vertical
<b>Optical Characteristics</b>	
Response Time	16 ms typical
Brightness	Typical: 300 cd/m <sup>2</sup> Default Calibrated: 200 cd/m <sup>2</sup>
Contrast ratio	1000:1 – typical
Palette	16.7 million – programmable gamma
DICOM Calibration	DICOM calibration validation via external photometer and Dome CXtra
Refresh Rate	
<b>Panel Interface</b>	
Digital Video Input	DVI Connector
Analog Video Input	VGA Connector
Digital Communication and ID	n/a
USB interface	n/a
<b>Video Input Formats</b>	
Landscape Orientation	1600 x 1200 24 bit color per pixel
Portrait Orientation	1200 x 1600 24 bit color per pixel
VGA/XGA	640 x 480 – 1024 x 768
<b>Calibration</b>	
Technique	Manual calibration with external photometer
Test Standards	
Calibration Type	DICOM Grayscale
<b>Imaging/Graphics Controller</b>	
Compatible Controller Support	AX4, NX285x16, NX285x1
<b>Physical Characteristics</b>	
Display Size without stand	13.8" x 17.5" x 2.8" (345mm x 445mm x 72mm)
Weight without stand	Less than 23lbs
Mounting Options	100 VESA mounting standard. Desktop stand with height, pivot, swivel and tilt adjustment
<b>Power Requirements</b>	
Power input	110 to 220 VAC, 50-60Hz Universal Auto Switching. 50 Watts typical, 1Watt standby
<b>Environmental</b>	
Operating Temperature Range	0 to 40 degrees C
<b>Certifications</b>	
Safety & Emission	Complies with CCC, CE, cUL, FCC Class B, MIC, TÜV GS, VCCI
<b>Service &amp; Support</b>	
Warranty	3-year standard warranty (w/48 hr. advanced exchange)

(Specifications may vary based on specific customized solution requirements.)

**North American Corporate Offices**

5750 Hellyer Avenue  
San Jose, CA 95138  
USA  
Tel: 408.776.0085  
Email: info@ndssi.com

**U.S. East Coast Office**

Dome Products  
400 Fifth Avenue  
Waltham, MA 02451  
Phone: -781-895-1155  
Fax: 781-895-1133  
Email: info@ndssi.com

**European Offices**

Nijverheidscentrum 28  
2761 JP Zevenhuizen (ZH)  
The Netherlands  
Tel: 31 180 63 43 56  
Email: info@ndssi.nl

**Asia Pacific Offices**

1st Fl., RISE Building,  
5-13, Asakusabashi 5-Chome,  
Taito-Ku, Tokyo, Japan, 111-0053  
Tel: 81 3 6420 3031  
Email: info@ndssi.jp

© 2008, NDS Surgical Imaging. Products may not be available in all markets and are subject to the regulatory or medical practices that govern individual markets. Always refer to the package insert, product label and/or user instructions before using any NDSSI product. Contact your NDSSI representative for more information. Products referenced with <sup>™</sup> designation are trademarks of NDSSI. Products referenced with <sup>®</sup> designation are registered trademarks of NDSSI.

